

FULL HD 1080P IP CAMERA WITH MIC



1. 1080P HD Low illumination resolution, clear and fine images;
2. Support multiple intelligent analysis;
3. Support 2D/3D noise reduction, digital wide dynamic;
4. Advanced H.265/H.264 video compression, Super low rate, high definition quality of image;
5. Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5;
6. Support ONVIF, access third party;
7. Support various mobile monitoring (iPhone, Android);
8. Provide web, CMS, center platform management software MYEYE, provide SDK development;
9. Support cloud technology, easy to achieve network penetration, for in-line and alarm information pushed.

Specification:

Model	WIP30S-MO30
Sensor	2.0M 1/2.8" IMX291 low illumination CMOS sensor
Day/Night	ICR
Min.Illumination	Low LUX: 0.0001LUX @F1.2 (Color) /0.00001LUX @F1.2 (B&W)
Lens	2.8mm fixed lens
IR LED	Φ8*6pcs
IR Distance	30M
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Electronic Shutter	1/50(60) s~ 1/10000s
Audio	Microphone
Alarm IO (optional)	
Alarm I/O	1/0 (support alarm input and video link to background)
VIDEO	
Compression	H.265 /H.264
Image output	Main stream: 1920*1080@25fps,1280*720@25fps; Sub-stream: 704*576@25fps;
Frame Rate	1-25FPS (Adjustable)
Bit Rate	100Kpbs~8Mpbs(Adjustable)
NETWORK	
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc.
ONVIF	Support
Intelligence analysis	Alarm line, alarm region, goods stranded, video block, fuzzy detection, scene change

Other function	Support WEB,OSD,live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software, MYEYE,perfect SDK;
PC Client & Browser	CMS/VMS, IE
Mobile Phone	iPhone,iPad,Android Mobile('XMeye' app)
INTERFACE	
Video Output	RJ45
LAN	1 RJ45 10/100 Ethernet port
GENERAL	
Working Temperature	-10 C ~ + 50 C
Working Humidity	0% ~ 90%
Power Supply	DC12V/POE
Dimension	106(φ)*72(H)mm
Weight	0.5Kg
Package	60pcs(59*38.5*40cm)