

# HD IP DOME CCTV CAMERA



## Increase Security With Our HD IP Dome CCTV Camera

An HD IP Dome CCTV Camera is a great choice to protect your home or business if you are looking for a lower-key, more covert camera. The dome also makes it harder for people to determine which way the camera inside is pointing, giving it seemingly more coverage than it actually has. Easy to install on either ceilings or walls, an HD IP Dome CCTV Camera is a great way to catch trespassers and thieves on camera both inside and out. With high-quality video (1080 resolution) and 'vandal proof' here at Revlight Security, we offer the best HD IP CCTV camera system with customizable options including:

- Embedded RTOS design, Dual Core 32 bit DSP
- H.265/H.264 dual-stream encoding
- Dual stream to adjust to the network flexibly
- Optional function: Poe, AUDIO.
- High quality with stable performance
- Free client software support for record, preview, playback
- Support P2P, NAT traversal and mobile monitor
- Support iPhone, iPad, Android Mobile
- Adjustable DOL- HDR
- 3D DNR, Privacy Mask, Motion Detection

- Open SDK support for industry customer's secondary development
- Support Onvif 2.4 protocol
- Support various network modes.

## Description

### Revlight Security's HD IP Dome CCTV Camera System Delivers Great Video Right To Your Handheld.

Our HD IP Dome CCTV Camera, when paired with a Network Video Recorder (NVR), give you, the user, optimal functionality. Whether you run security for a large corporation or just want to protect your home, with an NVR you can remain on the move while being able to see what is happening at home base. Download the user-friendly app and tap into your camera system from anywhere at any time.

## Specification

<b>Model</b>	WIPS20-AF15
<b>Sensor/DSP</b>	1/2.8", 2.0 Mega-Pixel CMOS IMX307/HISILICON Hi3516E
<b>Day/Night</b>	ICR
<b>Min.Illumination</b>	Low LUX: 0.1LUX (Color) /0.01LUX (B&W)
<b>Lens</b>	3.6mm Fixed Lens
<b>IR LED</b>	ø 8X6pcs
<b>IR Distance</b>	15m
<b>White Balance</b>	Manual/Automatic
<b>OSD</b>	YES
<b>Electronic Shutter</b>	1/2000 ~ 1/1000
<b>VIDEO</b>	
<b>Compression</b>	H.265/H.264
<b>Max Image Resolution</b>	1920*1080

<b>Frame Rate</b>	7-30FPS ( Adjustable)
<b>Bit Rate</b>	200Kpbs~8000kpbs(Adjustable)
AUDIO(Optional)	
NETWORK	
<b>Protocol</b>	TCP/IP, HTTP, DHCP, DNS, DDNS, UDP,RTSP, PPPoE, SMTP, NTP, UPnP, FTP,etc
<b>Compliance</b>	ONVIF 2.4
<b>PC Client &amp; Browser</b>	UC2, IE,seetong
<b>Mobile Phone</b>	iPhone,iPad,Android Mobile
INTERFACE	
<b>Video Output</b>	RJ45
<b>LAN</b>	1 RJ45 10/100 ethernet port
GENERAL	
<b>Working Temperature</b>	-10 C ~ + 50 C
<b>Working Humidity</b>	0% ~ 90%
<b>Power Supply</b>	DC12V ,1.0A
<b>Dimension</b>	111(W) x 84(H) mm
<b>Weight</b>	0.7Kg