



**4CH 1080N 5 in 1 XVR (AHD/TVI/CVI/CVBS/IP DVR)**

Picture



Model

**XVR-6104-2MP/ XVR-7104-2MP**

system

Processor

Hi35210D V200

system

Embedded LINUX operating system

system resource

Multi-channel real-time video, multi-channel real-time playback, multi-channel network operation, USB backup

interface

Operation interface

16-bit true color graphical user interface, support for mouse operation

Screen display

1./4.

Encoding

H.264

Monitor the quality

VGA / HDMI (up to 1080P)

Playback quality

1080N/960P/720P/960H/D1

Preview ability

4 \* 1080N @ 25 / 30fps (AHD / TVI / CVI) / 4 \* 960P five in one

Coding ability

4\* 1080N@25/30fps (5 in 1), 4 \* 720P @ 25fps (5 in 1)

Decoding capability

4 \* 1080N @ 25 / 30fps (five in one), 4 \* 960P @ 25fps (5 in 1)

Multi-mode input

Coaxial: 4 \* 1080N;  
Mixed: 3\*1080N (coaxial)+1\*1080P (network)  
Network: 8 \* 960P; 4 \* 1080P

Motion Detection

Each screen can be set 192 (16 \* 12) detection area; can be set multi-level sensitivity

Audio

Audio compression

G.711A

Two-way intercom

support

Video and playback

Video mode

Manual> Alarm> Motion Detection> Timing

Local playback (coaxial mode)

4

Storage and backup

Each drive occupies hard disk space

1080N / 720p ~ 20G / day \* channel; 960H 12 ~ 20G / day \* channel; Audio: 691.2M / day \* channel

Video preservation

Local hard disk, network

Backup method

Network backup, USB mobile hard drive, USB burning, SATA burning

Client

Client type

VMS

P2P

IOS、 Android 、 PC

APP function

Multi-screen monitoring, audio monitoring, cell phone video, capture, PTZ control, remote video playback, device list save

Coaxial visual control

Camera menu control

support

Interface

Video input

4\*BNC

Video output

1 VGA, 1 HDMI

Audio input

4 RCA

Audio output

1 RCA

Alarm input

/

Alarm output

/

Ethernet port

1\*10/100Mbps Ethernet port, RJ45 port

PTZ control

1\*RS485, Support for multiple PTZ protocol

USB

2 \*USB 2.0

HDD

1\*SATA interface (Up to 6TB)

Other

power

12V/2A

Consumption

<15W(Without HDD)

Dimension

330\*256\*88

Weight

1.2KG

Temperature

-10 °C~ +55 °C

Humidity

10%~90%