

FISHEYE 360 DEGREES IP CAMERA



1. UP to 5 megapixel resolution(2592×1944)
2. Max 30fps@5MP(2592×1944),60fps@2MP(1920×1080)
3. H.265 MainProfile, H.264 Baseline/MainProfile/HighProfile
4. WDR
5. Day/Night(ICR)&3D DNR&AWB&AGC&BLC
6. Fisheye Lens
7. Support mobile phone monitoring and P2P function
8. PoE function
9. IP66 rating

Specification:

Camera	
Media Processor	High-performance Hisilicon DSP
Image Sensor	1/1.8" 5MP progressive scan CMOS
Shuttle time	1/5s to 1/50,000s
Min Illumination	Color : 0.2 Lux /F1.2 B/W : 0.003 Lux / F1.2;0Lux IR On
Fisheye Lens	1.57mm
Day&Night	IR cut filter with auto switch
Compression	
Video Compression	H.265/H.264/MJPEG
Coding standard	H.265 MainProfile, H.264 Baseline/MainProfile/HighProfile,
Image	
Max Image Size	2592(H)×1944(V)
Stream	Dual-stream
Frame Rate	Main Stream : 30fps @(2592 × 1944),60fps @(1920 × 1080) Sub-stream : 30fps (640 × 480);
Network	
Alarm Trigger	Motion detection, tampering alarm, network disconnect, storage exception
Protocols	IPv4/IPv6、RTSP/RTP/RTCP、TCP/UDP、HTTP、DHCP、DNS、FTP、DDNS、PPPoE、SMTP、QOS、Onvif
Onvif	V2.4 Version
Browser	IE(8、9、10、11),Chrome,Firefox,Safaribetc,etc
Software Development Kit	Linux/Windows C++/C SDK
Interface	
Network	1 RJ45 10M/100M adaptive Ethernet port

Reset	A reset button (press and hold 3 seconds valid)
General Specifications	
Operating Conditions	-40°C ~ 60°C, humidity less than 95%
Power Supply	DC12V±10%, PoE (802.3af)
Power Consumption	2.5W
Weather proof rating	IP66
Dimensions(mm)	103×103×60
Weight(kg)	0.3

