



8CH 1080N 5 in 1 XVR (AHD/TVI/CVI/CVBS/IP DVR)

Picture



Model

XVR-6108-2MP/XVR-7108-2MP

system

Processor

Hi3520DV300

system

Embedded LINUX operating system

system resource

Multi-channel real-time video, multi-channel real-time playback, multi-channel network operation, USB backup

interface

Operation interface

16-bit true color graphical user interface, support for mouse operation

Screen display

1/4/6/8

video

Encoding

H.264

Monitor the quality

VGA / HDMI (up to 1080P)

Playback quality

1080N/960P/720P/960H/D1

Preview ability

8 * 1080N @ 25 / 30fps (AHD / TVI / CVI) / 8 * 960P five in one

Coding ability

8 * 1080N @ 12fps (five in one), 8 * 720P @ 12fps (five in one)

Decoding capability

4* 1080N@12fps (5 in 1), 4 * 960P @ 25fps (5 in 1), 8*D 1 (5 in 1)

Multi-mode input

Coaxial: 8*1080N;
Mixed: 4 * 1080N (coaxial) + 4 * 960P (network)
Network: 16*960P;8*1080P;4*3M

Motion Detection

Each screen can be set 192 (16 * 12) detection area; can be set multi-level sensitivity

Audio

Audio compression

G.711A

Two-way intercom

support

Video and playback

Video mode

Manual> Alarm> Motion Detection> Timing

Local playback (coaxial mode)

4 (optional 8 way)

Storage and backup

Each drive occupies hard disk space

1080N / 720p ~ 20G / day * channel; 960H 12 ~ 20G / day * channel; Audio: 691.2M / day * channel

Video preservation

Local hard disk, network

Backup method

Network backup, USB mobile hard drive, USB burning, SATA burning

Client

Client type

VMS

P2P

IOS、Android、PC

APP function

Multi-screen monitoring, audio monitoring, cell phone video, capture, PTZ control, remote video playback, device list save

Coaxial visual control

Camera menu control

support

Interface

Video input

8*BNC

Video output

1 VGA, 1 HDMI

Audio input

4 RCA

Audio output

1 RCA

Alarm input

/

Alarm output

/

Ethernet port

1*10/100Mbps Ethernet port, RJ45 port

PTZ control

1*RS485, Support for multiple PTZ protocol

USB

2 *USB 2.0

HDD

1*SATA interface (Up to 6TB)

Other

power

12V/2A

Consumption

<15W(Without HDD)

Dimension

330*256*88

Weight

1.2KG

Temperature

-10 °C~ +55 °C

Humidity

10%~90%